

GHIM HYDRAULICS SRL

Via dell'Industria, 40
25030 ERBUSCO — BS — ITALY
Tel. +39.030.7704623 (4 linee r.a.)
Fax. +39.030.7704886
Web: www.ghim.it
Mail: info@ghim.it



HYDRAULIC COMPONENTS

POMPE A MANO
HAND PUMPS
TANK



*Work with us
and we will grow
Together....*

Catalogue: AEP - Edition 10.2011 - Liv. AA

CODIFICA POMPE A MANO - HAND PUMPS CODING

A E P - X Y - K G N N

AEP	XY	K	G	NN
SERIES	TYPE	CONFIGURATION	SPECIAL OPTIONAL	CAPACITY Cc/CYCLE
AL SERIES	98 "AL-HPE" - WITH KNOB	K = 1 VERSIONE BASE STANDARD VERSION	G=0 STANDARD	06 = 6 CC
	94 "AL-HPH" - WITH DISTRIBUTOR			12 = 12 CC
	93 "AL-HPI" WITH DISTRIBUTOR			25 = 25 CC
	M3 "AL-HPI-MARINE" WITH DISTRIBUTOR			45 = 45 CC
	96 "AL-HPM" WITH KNOB - DOUBLE ACTING			20 = 20 CC
	91 "AL-HPR" WITH KNOB - DOUBLE ACTING			50 = 50 CC
	M1 "AL-HPR-MARINE" WITH KNOB			70 = 70 CC
	99 "AL-HPS" FOR MANIFOLD - DOUBLE ACTING			
	M9 "AL-HPS-MARINE" - FOR MANIFOLD			
	95 "AL-HPT" WITH KNOB - DOUBLE ACTING			
	M5 "AL-HPT-MARINE" WITH KNOB			
	97 "AL-HPV" DOUBLE FLOW BP - AP			
	92 "AL-HPW" FOR MANIFOLD - SINGLE ACTING			
	90 "AL-HPY" DOUBLE FLOW BP - AP			
GW SERIES	88 "GW-HPE" WITH KNOB - SINGLE ACTING	K = 3 VERSIONE CON SOFFIETTO VERSION WITH BELLOWS	G=0 STANDARD	
	84 "GW-HPH" WITH DISTRIBUTOR			
	83 "GW-HPI" WITH DISTRIBUTOR			
	F3 "GW-HPI-FROST" WITH DISTRIBUTOR			
	W3 "GW-HPI-WITON" WITH DISTRIBUTOR			
	81 "GW-HPR" WITH KNOB - DOUBLE ACTING			
	F1 "GW-HPR-FROST" WITH KNOB			
	W1 "GW-HPR-WITON" WITH KNOB			
	89 "GW-HPS" FOR MANIFOLD - DOUBLE ACTING			
	85 "GW-HPT" WITH KNOB - DOUBLE ACTING			
	F5 "GW-HPT-FROST" WITH KNOB			
	W5 "GW-HPT-WITON" WITH KNOB			
	87 "GW-HPV" DOUBLE FLOW BP - AP			
	82 "GW-HPW" MANIFOLD - SINGLE ACTING			
	80 "GW-HPY" DOUBLE FLOW BP - AP			
	GH SERIES			79 "GH-HPB" DOUBLE PILOT RETAIN VALVE
77 "GH-HPE" WITH KNOB - SINGLE ACTING				
73 "GH-HPI" WITH DISTRIBUTOR				
75 "GH-HPM" DOUBLE ACTING				
71 "GH-HPR" WITH KNOB - DOUBLE ACTING				
PC "GH-HPW-CC" WITH CYLINDER				
HP "GH-HPX-HP" HIGH-PRESSURE				
PD "GH-HPY-PD" PEDALE - FOOT				
		K = 7 VERSIONE CON SOFFIETTO E VALVOLA DI MASSIMA VERSION WITH RELIEF VALVE AND BELLOW		
		K = 9 (-) SPECIAL VERSION UNDER CUSTOMER SPECIFICATIONS		

Note: